# NSN 5305-00-918-4942

Machine Screw - Page 1 of 2





Thread Class:

2a

**Thread Direction:** 

**Right-hand** 

### Thread Length:

Between 0.270 inches and 0.312 inches

#### Fastener Length:

Between 0.281 inches and 0.312 inches

#### Head Style:

Fillister

Head Diameter:

Between 0.166 inches and 0.183 inches

#### **Head Height:**

Between 0.072 inches and 0.079 inches

### Hole Diameter:

0.037 inches

Internal Drive Style:

Slot

**Thread Diameter:** 

0.112 inches

#### **Hole Quantity:**

1

### Thready Qty Per Inch (tpi):

48

## Min. Tensile Strength (psi):

80000 pounds per square inch

## Screw Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

## Screw Material Specification:

66 federal standard all material responses

## Screw Surface Treatment:

Passivate

## Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## Head Hole Configuration Style:

Round

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5305-00-918-4942

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

