NSN 5305-00-919-5080

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-919-5080

3aThread Direction:Right-handThread Length:0.375 inchesFastener Length:Between 0.922 inches and 0.952 inchesHead Style:Flat countersunkHead Diameter:Between 0.577 inches and 0.635 inchesGrip Diameter:Between 0.3110 inches and 0.3120 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.312 inchesGrip Length:0.562 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):
Right-handThread Length:0.375 inchesFastener Length:Between 0.922 inches and 0.952 inchesHead Style:Flat countersunkHead Diameter:Between 0.577 inches and 0.635 inchesGrip Diameter:Between 0.3110 inches and 0.3120 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.312 inchesGrip Length:0.562 inchesThready Qty Per Inch (tpi):24
Thread Length:0.375 inchesFastener Length:Between 0.922 inches and 0.952 inchesHead Style:Flat countersunkHead Diameter:Between 0.577 inches and 0.635 inchesGrip Diameter:Between 0.3110 inches and 0.3120 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.312 inchesGrip Length:0.562 inchesThready Qty Per Inch (tpi):24
0.375 inches Fastener Length: Between 0.922 inches and 0.952 inches Head Style: Flat countersunk Head Diameter: Between 0.577 inches and 0.635 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.312 inches Grip Length: 0.562 inches Thready Qty Per Inch (tpi): 24
Fastener Length:Between 0.922 inches and 0.952 inchesHead Style:Flat countersunkHead Diameter:Between 0.577 inches and 0.635 inchesGrip Diameter:Between 0.3110 inches and 0.3120 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.312 inchesGrip Length:0.562 inchesThready Qty Per Inch (tpi):24
Between 0.922 inches and 0.952 inches Head Style: Flat countersunk Head Diameter: Between 0.577 inches and 0.635 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.312 inches Grip Length: 0.562 inches Thready Qty Per Inch (tpi): 24
Head Style:Flat countersunkHead Diameter:Between 0.577 inches and 0.635 inchesGrip Diameter:Between 0.3110 inches and 0.3120 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.312 inchesGrip Length:0.562 inchesThready Qty Per Inch (tpi):24
Flat countersunk Head Diameter: Between 0.577 inches and 0.635 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.312 inches Grip Length: 0.562 inches Thready Qty Per Inch (tpi): 24
Head Diameter:Between 0.577 inches and 0.635 inchesGrip Diameter:Between 0.3110 inches and 0.3120 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.312 inchesGrip Length:0.562 inchesThready Qty Per Inch (tpi):24
Between 0.577 inches and 0.635 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.312 inches Grip Length: 0.562 inches Thready Qty Per Inch (tpi): 24
Grip Diameter: Between 0.3110 inches and 0.3120 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.312 inches Grip Length: 0.562 inches Thready Qty Per Inch (tpi): 24
Between 0.3110 inches and 0.3120 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.312 inches Grip Length: 0.562 inches Thready Qty Per Inch (tpi): 24
Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.312 inches Grip Length: 0.562 inches Thready Qty Per Inch (tpi): 24
Offset cruciform (torque set) Thread Diameter: 0.312 inches Grip Length: 0.562 inches Thready Qty Per Inch (tpi): 24
Thread Diameter: 0.312 inches Grip Length: 0.562 inches Thready Qty Per Inch (tpi): 24
0.312 inches Grip Length: 0.562 inches Thready Qty Per Inch (tpi): 24
Grip Length: 0.562 inches Thready Qty Per Inch (tpi): 24
0.562 inches Thready Qty Per Inch (tpi): 24
Thready Qty Per Inch (tpi): 24
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Titanium alloy uns r54520
Material Specification:
Nas 621, 6al-4v assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1155 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-00-919-5080

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

