

View Online at <https://aerobasegroup.com/nsn/5305-00-919-7860>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.203 inches and 0.235 inches

Fastener Length:

Between 0.658 inches and 0.681 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.302 inches and 0.322 inches

Head Height:

Between 0.085 inches and 0.096 inches

First Diameter From Head:

Between 0.099 inches and 0.119 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.423 inches and 0.478 inches

Internal Drive Style:

Slot

Thread Diameter:

0.164 inches

Thread Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347

Material Specification:

Qq-s-763 federal specification all material responses or 66 federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0