## NSN 5305-00-920-0560

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-920-0560

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.276 inches
Fastener Length:
Between 0.449 inches and 0.479 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.328 inches and 0.385 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Shank Unthreaded Hole Diameter:
0.070 inches first hole
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Grip Length:
0.188 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Distance From Head Largest Bearing Surface To Shank Hole Center:
0.347 inches first hole
Surface Finish:
32.0 microinches threads
Material:
Titanium alloy
Material Specification:
Nas 621 assn standard single material response
Thread Series Designator:
Unjf

**Specification Data:** 

80205-nas1153 professional/industrial association standard

## NSN 5305-00-920-0560

Close Tolerance Screw - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0