NSN 5305-00-920-0568

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-920-0568

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.276 inches
Fastener Length:
Between 1.386 inches and 1.416 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.280 inches and 0.327 inches
Grip Diameter:
Between 0.1625 inches and 0.1635 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.164 inches
Grip Length:
1.125 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Occurtancials Aurales
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Between 99.0 degrees and 101.0 degrees
Between 99.0 degrees and 101.0 degrees Surface Finish:
Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads
Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material:
Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment:
Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate
Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification:
Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 3 federal specification single treatment response
Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 3 federal specification single treatment response Thread Series Designator:
Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 3 federal specification single treatment response Thread Series Designator: Unjc

N/a

NSN 5305-00-920-0568

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0