

View Online at <https://aerobasegroup.com/nsn/5305-00-920-9957>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.287 inches and 0.327 inches

Fastener Length:

Between 3.076 inches and 3.116 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.182 inches and 0.192 inches

Head Height:

Between 0.420 inches and 0.450 inches

First Diameter From Head:

Between 0.147 inches and 0.149 inches

Second Diameter From Head:

Between 0.182 inches and 0.192 inches

Third Diameter From Head:

Between 0.120 inches and 0.130 inches

Fourth Diameter From Head:

Between 0.245 inches and 0.255 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.070 inches and 0.090 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.137 inches and 0.147 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 2.635 inches and 2.648 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

Between 2.677 inches and 2.683 inches

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

4

Material:

Steel comp 303 or steel comp 304

Material Specification:

Astm a582 assn standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.