Externally Relieved Body Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-922-1733

| Thread Class: | |
|---|--|
| Ja | |
| Sa Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 0.180 inches | |
| | |
| Fastener Length: | |
| Between 0.423 inches and 0.453 inches | |
| Head Style: | |
| Pan Lionaton | |
| Head Diameter: | |
| Between 0.256 inches and 0.270 inches | |
| Head Height: | |
| Between 0.087 inches and 0.097 inches | |
| First Diameter From Head: | |
| Between 0.090 inches and 0.100 inches | |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: | |
| Between 0.243 inches and 0.273 inches | |
| Internal Drive Style: | |
| Cross recess type 1 | |
| Thread Diameter: | |
| 0.138 inches | |
| Thready Qty Per Inch (tpi): | |
| | |
| Externally Relieved Body Diameter Quantity: | |
| 1 Material: | |
| | |
| Stainless steel | |
| Surface Treatment: | |
| Passivate | |
| Surface Treatment Specification: | |
| -q-p-35 federal specification single treatment response | |
| Thread Series Designator: | |
| Unjc Shelf Life: | |
| | |
| N/a Unit Of Measure: | |
| | |
| Domilitarization | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A003b0 | |