NSN 5305-00-922-1804

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-922-1804

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.178 inches and 0.266 inches
Fastener Length:
Between 0.234 inches and 0.266 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.262 inches and 0.270 inches
Head Height:
Between 0.159 inches and 0.164 inches
Hole Diameter:
0.047 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.164 inches
Width Across Flats:
Between 0.141 inches and 0.143 inches
Hole Quantity:
4
Ноlе Туре:
Drilled
Thready Qty Per Inch (tpi):
36
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
155000 pounds per square inch
Hole Configuration Style:
Round longitudinal hole
Material:
Steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Ams-qq-p-416, type 2, cl 2 federal specification all treatment responses

NSN 5305-00-922-1804

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0