## NSN 5305-00-922-4959

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-922-4959 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.080 inches **Fastener Length:** 0.345 inches **Head Style:** Hexagon **Head Height:** Between 0.049 inches and 0.060 inches Width Between Flats: Between 0.181 inches and 0.187 inches Point Length: 0.025 inches First Diameter From Head: Between 0.076 inches and 0.080 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.240 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** 120.0 degrees Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Astm a380 assn standard single treatment response

Unc

**Thread Series Designator:** 

## NSN 5305-00-922-4959

Externally Relieved Body Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0