NSN 5305-00-922-9030

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-922-9030 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.230 inches and 0.270 inches **Fastener Length:** Between 0.302 inches and 0.322 inches **Head Style:** Hexagon **Head Height:** Between 0.146 inches and 0.166 inches Width Between Flats: Between 0.430 inches and 0.439 inches **First Diameter From Head:** Between 0.185 inches and 0.195 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.062 inches and 0.072 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Externally Relieved Body Diameter Quantity:** Material: Steel comp 8740 **Material Specification:** Ams 6322 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams 2400 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-922-9030

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0