NSN 5305-00-923-1120

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-923-1120

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.329 inches and 0.385 inches |
| Fastener Length: |
| Between 0.365 inches and 0.385 inches |
| Head Style: |
| Double hexagon extended washer |
| Head Height: |
| Between 0.240 inches and 0.260 inches |
| Width Between Flats: |
| Between 0.212 inches and 0.220 inches |
| Extended Washer Diameter: |
| Between 0.302 inches and 0.322 inches |
| Extended Washer Thickness: |
| Between 0.030 inches and 0.040 inches |
| Hole Diameter: |
| 0.047 inches |
| Thread Diameter: |
| 0.164 inches |
| Hole Quantity: |
| 4 |
| Thready Qty Per Inch (tpi): |
| 36 |
| Min. Tensile Strength (psi): |
| 140000 pounds per square inch |
| Hardness Rating: |
| Between 248.0 brinell standard and 321.0 brinell standard |
| Screw Material: |
| Iron alloy 660 |
| Screw Material Specification: |
| Ams 5735 assn standard single material response |
| Head Hole Configuration Style: |
| Hexagon longitudinal hole |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| <u></u> |

NSN 5305-00-923-1120

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0