NSN 5305-00-923-8599



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-923-8599 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.418 inches and 0.438 inches **Fastener Length:** Between 2.168 inches and 2.188 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.419 inches and 0.437 inches **Head Height:** Between 0.209 inches and 0.219 inches **Shoulder Diameter:** 0.3085 inches first shoulder and 0.3105 inches first shoulder **Shoulder Length:** 1.750 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 140000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 43.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:**

Unc

Shelf Life:

N/a

NSN 5305-00-923-8599

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0