NSN 5305-00-925-0648

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-925-0648 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.230 inches and 0.270 inches **Fastener Length:** Between 0.645 inches and 0.675 inches **Head Style:** Hexagon **Head Height:** 0.160 inches Width Between Flats: Between 0.370 inches and 0.380 inches **First Diameter From Head:** Between 0.135 inches and 0.145 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.330 inches and 0.410 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 95000 pounds per square inch Hardness Rating: 207.0 brinell standard and 212.0 brinell standard **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Point style no. 7 0.035 in. Min, 0.045 in. Maximum Ig, 119.5 to 120.5 degrees of chamfered angle Material: Steel comp 430f **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unf

NSN 5305-00-925-0648

Externally Relieved Body Screw - Page 2 of 2



N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0