Unf

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-925-0648

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.230 inches and 0.270 inches
Fastener Length:
Between 0.645 inches and 0.675 inches
Head Style:
Hexagon
Head Height:
0.160 inches
Width Between Flats:
Between 0.370 inches and 0.380 inches
First Diameter From Head:
Between 0.135 inches and 0.145 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.330 inches and 0.410 inches
Internal Drive Style:
Slot
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
95000 pounds per square inch
Hardness Rating:
207.0 brinell standard and 212.0 brinell standard
Externally Relieved Body Diameter Quantity:
1
Special Features:
Point style no. 7 0.035 in. Min, 0.045 in. Maximum lg, 119.5 to 120.5 degrees of chamfered angle
Material:
Steel comp 430f
Material Specification:
Astm a582 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
11-4

NSN 5305-00-925-0648

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0