NSN 5305-00-925-4772

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-925-4772

| Thread Class: |
|---|
| За |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.316 inches |
| Fastener Length: |
| Between 2.051 inches and 2.081 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.449 inches and 0.507 inches |
| Grip Diameter: |
| Between 0.2485 inches and 0.2495 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| 1.750 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Titanium alloy uns r54520 |
| Material Specification: |
| Nas 621, 6al-4v assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas1 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5305-00-925-4772

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

