## NSN 5305-00-925-4838

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-925-4838 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.265 inches and 0.406 inches **Fastener Length:** Between 0.391 inches and 0.438 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 8630 or steel comp 4037 **Screw Material Specification:** Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification all treatment responses **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A500d0

## NSN 5305-00-925-4838

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.