NSN 5305-00-926-5652

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-926-5652 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.350 inches and 0.380 inches **Fastener Length:** Between 0.350 inches and 0.380 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037 **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification all treatment responses **Thread Series Designator:** Unf **Specification Data:** 80205-nas604 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A500d0