## NSN 5305-00-926-5707

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-926-5707

| view Online at https://aerobasegroup.com/nsn/5305-00-926-570 |
|--|
| Thread Class:  |
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.251 inches and 0.301 inches                        |
| Fastener Length:   |
| Between 1.199 inches and 1.229 inches                        |
| Head Style:  |
| Pan no. 2  |
| Head Diameter:   |
| Between 0.357 inches and 0.373 inches                        |
| Head Height:   |
| Between 0.122 inches and 0.133 inches                        |
| Grip Diameter:   |
| Between 0.1885 inches and 0.1895 inches                      |
| Internal Drive Style:  |
| Offset cruciform (torque set)                                |
| Thread Diameter:   |
| 0.190 inches   |
| Grip Length:   |
| Between 0.928 inches and 0.948 inches                        |
| Thready Qty Per Inch (tpi):                                  |
| 32   |
| Min. Tensile Strength (psi):                                 |
| 140000 pounds per square inch                                |
| Hardness Rating:   |
| 36.0 rockwell c and 40.0 rockwell c                          |
| Surface Finish:  |
| 32.0 microinches threads                                     |
| Product Name:  |
| Navy special project   |
| Material:  |
| Iron alloy 660   |
| Surface Treatment:   |
| Plastic  |
| Surface Treatment Specification:                             |
| A0110-006 fscm 43999 mfr ref single treatment response       |
| Thread Series Designator:                                    |
| Unf  |
| Specification Data:  |
| 80205-nas1133 professional/industrial association standard   |

80205-nas1133 professional/industrial association standard

## NSN 5305-00-926-5707

Close Tolerance Screw - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0