NSN 5305-00-926-5707

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-926-5707

view Online at https://aerobasegroup.com/nsn/5305-00-926-570
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.251 inches and 0.301 inches
Fastener Length:
Between 1.199 inches and 1.229 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.357 inches and 0.373 inches
Head Height:
Between 0.122 inches and 0.133 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Grip Length:
Between 0.928 inches and 0.948 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
140000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
32.0 microinches threads
Product Name:
Navy special project
Material:
Iron alloy 660
Surface Treatment:
Plastic
Surface Treatment Specification:
A0110-006 fscm 43999 mfr ref single treatment response
Thread Series Designator:
Unf
Specification Data:
80205-nas1133 professional/industrial association standard

80205-nas1133 professional/industrial association standard

NSN 5305-00-926-5707

Close Tolerance Screw - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0