## NSN 5305-00-926-6656

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-926-6656 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.418 inches and 0.480 inches **Fastener Length:** Between 1.144 inches and 1.175 inches **Head Style:** Flat chamfer **Head Diameter:** 0.280 inches **Head Height:** Between 0.075 inches and 0.085 inches **First Diameter From Head:** 0.165 inches **Second Diameter From Head:** 0.095 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.118 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.664 inches and 0.695 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303 **Material Specification:** Qq-s-764, cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

## NSN 5305-00-926-6656

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0