

NSN 5305-00-927-1462 Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-927-1462 **Thread Class:** За **Thread Direction:**

Right-hand Thread Length: Between 0.092 inches and 0.097 inches **Fastener Length:** Between 0.140 inches and 0.145 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** 0.105 inches **Hole Diameter:** 0.037 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.093 inches and 0.095 inches **Hole Quantity:** 2 **Hole Type:** Drilled

Thready Qty Per Inch (tpi):

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 43.0 rockwell c

Hole Configuration Style:

Round

Surface Finish:

32.0 microinches

Material:

Stainless steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification all treatment responses

NSN 5305-00-927-1462

Socket Head Cap Screw - Page 2 of 2



Fiig: A003b0