

View Online at <https://aerobasegroup.com/nsn/5305-00-928-7045>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.170 inches and 0.250 inches

Fastener Length:

Between 0.220 inches and 0.250 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.218 inches and 0.226 inches

Head Height:

Between 0.134 inches and 0.138 inches

Hole Diameter:

Between 0.033 inches and 0.039 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.138 inches

Width Across Flats:

Between 0.109 inches and 0.111 inches

Hole Quantity:

2

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Hole Configuration Style:

Round internal hexagon

Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0