NSN 5305-00-928-7089

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-928-7089 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.391 inches **Fastener Length:** Between 1.938 inches and 1.968 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.704 inches and 0.762 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.375 inches **Grip Length:** 1.562 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Titanium alloy uns r54520 **Material Specification:** Nas621, comp 6al-4v assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1156 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Unit Of Measure:
-Demilitarization:

NSN 5305-00-928-7089

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0