Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-928-9567

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.438 inches |
| Fastener Length: |
| 0.938 inches |
| Head Style: |
| Knurled no. 1 |
| Head Diameter: |
| 0.562 inches |
| Head Height: |
| 0.250 inches |
| First Diameter From Head: |
| 0.185 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.500 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.250 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Mil-s-7720 military specification single material response |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |



Mil-std (military Standard):

Mil-s-7720 spec.