NSN 5305-00-928-9569

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-928-9569 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.121 inches and 0.188 inches **Fastener Length:** Between 0.157 inches and 0.188 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.136 inches and 0.140 inches **Head Height:** Between 0.044 inches and 0.053 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 140000 pounds per square inch Hardness Rating: Between 248.0 brinell standard and 321.0 brinell standard **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5735 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1101 professional/industrial association standard

Shelf Life:
N/a
Unit Of Measure:
-Demilitarization:
No

NSN 5305-00-928-9569

Machine Screw - Page 2 of 2



Fiig:

A500d0