NSN 5305-00-929-4070

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-929-4070 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.276 inches **Fastener Length:** Between 0.573 inches and 0.603 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.296 inches and 0.313 inches **Head Height:** Between 0.103 inches and 0.118 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** 0.312 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 140000 pounds per square inch Hardness Rating: 248.0 brinell standard and 321.0 brinell standard **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** -a0110-006 fscm 43999 mfr ref single treatment response **Thread Series Designator:** Unjf

Specification Data:

80205-nas1123 professional/industrial association standard

NSN 5305-00-929-4070

Close Tolerance Screw - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0