## NSN 5305-00-929-4093

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-929-4093

3a Thread Direction: Right-hand Thread Length: 0.316 inches Fastener Length: Between 1.801 inches and 1.831 inches Head Style: Flat countersunk Head Diameter: Between 0.499 inches and 0.507 inches Grip Diameter: Between 0.499 inches and 0.2495 inches Grip Diameter: 0.2485 inches and 0.2495 inches Hernal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.250 inches Grip Length: 1.500 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 9.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Thread Streis Designator: Nas 621, 6al-4v assn standard single material response Thread Streis Designator: Unjf Spacification Data: 80205-nas1154 professional/industrial association standard Shef Life: Na	Thread Class:
Right-hand         Thread Length:         0.316 inches         Fastener Length:         Between 1.801 inches and 1.831 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.499 inches and 0.507 inches         Grip Diameter:         Between 0.498 inches and 0.2495 inches         Internal Drive Style:         Offset cruciform (torque set)         Thread Diameter:         0.250 inches         Grip Length:         1.500 inches         Thready Qty Per Inch (tpi):         28         Min. Tensile Strength (psi):         160000 pounds per square inch         Courtersink Angle:         Between 99.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material:         Thread Specification:         Nas 621, 6al-4v assn standard single material response         Thread Specification:         Nas 621, 6al-4v assn standard single material response         Thread Specification Data:         80205-nas1154 professional/industrial association standard         Suffication Data:         Na'         Unit of Measure:	3a
Tread Length:         0.316 inches         Fastener Length:         Between 1.801 inches and 1.831 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.499 inches and 0.507 inches         Grip Diameter:         Between 0.2485 inches and 0.2495 inches         Internal Drive Style:         Offset cruciform (torque set)         Thread Diameter:         0.250 inches         Grip Length:         1.500 inches         Thready Qty Per Inch (tpi):         28         Min. Tensile Strength (psi):         160000 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material         Thread Series Designator:         Unif         Specification Data:         80205-nas1154 professional/industrial association standard         Surface Finis:         30205-nas1154 professional/industrial association standard         Sheff Life:         N/a         Lift of Measure:	Thread Direction:
0.316 inchesFastener Length:Between 1.801 inches and 1.831 inchesHead Style:Flat countersunkHead Diameter:Between 0.499 inches and 0.507 inchesGrip Diameter:Between 0.2485 inches and 0.2495 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.250 inchesGrip Length:1.500 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:32.0 microinches threadsMaterial:Titanium alloy uns r54520MaterialMaterial Specification:Nas 621, 6al-4v assn standard single material responseThread Series Designator:UnifSpecification Data:80205-nas1154 professional/industrial association standardMief Life:N/aLitof Measure:NaLitof Measure:Litof Measure:Li	Right-hand
Fastener Length:         Between 1.801 inches and 1.831 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.499 inches and 0.507 inches         Grip Diameter:         Between 0.2485 inches and 0.2495 inches         Internal Drive Style:         Offset cruciform (torque set)         Thread Diameter:         0.250 inches         Grip Length:         1.500 inches         Thready Qty Per Inch (tpi):         28         Min. Tensile Strength (psi):         160000 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 10.10 degrees         Surface Finish:         32.0 microinches threads         Material:         Titanium alloy uns r54520         Material Specification:         Nas 621, 6al-4v assn standard single material response         Thread Series Designator:         Unjf         Specification Data:         80205-nas1154 professional/industrial association standard         Sheft Life:         N/a         Unit Of Measure:	Thread Length:
Between 1.801 inches and 1.831 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.499 inches and 0.507 inches         Grip Diameter:         Between 0.2485 inches and 0.2495 inches         Internal Drive Style:         Offset cruciform (torque set)         Thread Diameter:         0.250 inches         Grip Length:         1.500 inches         Thready Qty Per Inch (tpi):         28         Min. Tensile Strength (psi):         160000 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material:         Titanium alloy uns r54520         Material Specification:         Nas 621, 6al-4v assn standard single material response         Thread Series Designator:         Unjf         Specification Data:         80205-nas1154 professional/industrial association standard         Sheft Life:         N/a         Unit Of Measure:	0.316 inches
Head Style:         Flat countersumk         Head Diameter:         Between 0.499 inches and 0.507 inches         Grip Diameter:         Between 0.2485 inches and 0.2495 inches         Internal Drive Style:         Offset cruciform (torque set)         Thread Diameter:         0.250 inches         Grip Length:         1.500 inches         Thready Qty Per Inch (tpi):         28         Min. Tensile Strength (psi):         160000 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material:         Titanium alloy uns r54520         Material Specification:         Nas 621, 6al-4v assn standard single material response         Thread Series Designator:         Unjf         Specification Data:         80205-nas1154 professional/industrial association standard         Sheft Life:         N/a         Unit Of Measure:	Fastener Length:
Flat countersunk         Head Diameter:         Between 0.499 inches and 0.507 inches         Grip Diameter:         Between 0.2485 inches and 0.2495 inches         Internal Drive Style:         Offset cruciform (torque set)         Thread Diameter:         0.250 inches         Grip Length:         1.500 inches         Thready Qty Per Inch (tpi):         28         Min. Tensile Strength (psi):         160000 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material:         Titanium alloy uns r54520         Material         Sus 621, 6al-4v assn standard single material response         Thread Series Designator:         Unif         Specification Data:         Na         Di205-nas1154 professional/industrial association standard         Shelf Life:         N/a         Unit Of Measure:	Between 1.801 inches and 1.831 inches
Head Diameter: Between 0.499 inches and 0.507 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.250 inches Grip Length: 1.500 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy uns r54520 Material Specification: Nas 621, 6al-4v assn standard single material response Thread Series Designator: Unjf Specification Data: 80205-nas1154 professional/industrial association standard Shelf Life: N/a Unit Of Measure:	Head Style:
Between 0.499 inches and 0.507 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.250 inches Grip Length: 1.500 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Ttanium alloy uns r54520 Material Specification: Nas 621, 6al-4v assn standard single material response Thread Series Designator: Unjf Specification Data: 80205-nas1154 professional/industrial association standard Shelf Life: N/a Unit Of Measure:	Flat countersunk
Grip Diameter:Between 0.2485 inches and 0.2495 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.250 inchesGrip Length:1.500 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches threadsMaterial:Titanium alloy uns r54520Material Specification:LogfSpecification Data:Bo205-nas1154 professional/industrial association standardShelf Life:N/aUnit Of Measure:	Head Diameter:
Between 0.2485 inches and 0.2495 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.250 inches Grip Length: 1.500 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy uns r54520 Material Specification: Nas 621, 6al-4v assn standard single material response Thread Series Designator: Unif Specification Data: 80205-nas1154 professional/industrial association standard Shelf Life: N/a Unit Of Measure:	Between 0.499 inches and 0.507 inches
Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.250 inches Grip Length: 1.500 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy uns r54520 Material Specification: Nas 621, 6al-4v assn standard single material response Thread Series Designator: Unjf Specification Data: 80205-nas1154 professional/industrial association standard Shelf Life: N/a Unit Of Measure:	Grip Diameter:
Offset cruciform (torque set) Thread Diameter: 0.250 inches Grip Length: 1.500 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy uns r54520 Material Specification: Nas 621, 6al-4v asın standard single material response Thread Series Designator: Unjf Specification Data: 80205-nas1154 professional/industrial association standard Ashef Life: N/a Unit Of Measure:	Between 0.2485 inches and 0.2495 inches
Thread Diameter:0.250 inchesGrip Length:1.500 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches threadsMaterial:Titanium alloy uns r54520Material Specification:Nas 621, 6al-4v assn standard single material responseThread Series Designator:UnifSpecification Data:80205-nas1154 professional/industrial association standardShelf Life:N/aUnit Of Measure:	Internal Drive Style:
0.250 inches Grip Length: 1.500 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: 32.0 microinches threads Material: Titanium alloy uns r54520 Material Specification: Nas 621, 6al-4v assn standard single material response Thread Series Designator: Unjf Specification Data: 80205-nas1154 professional/industrial association standard Shelf Life: N/a Unit Of Measure:	Offset cruciform (torque set)
Grip Length: 1.500 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: 32.0 microinches threads Material: Titanium alloy uns r54520 Material Specification: Nas 621, 6al-4v assn standard single material response Thread Series Designator: Unjf Specification Data: 80205-nas1154 professional/industrial association standard Shelf Life: N/a Unit Of Measure:	Thread Diameter:
1.500 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy uns r54520 Material Specification: Nas 621, 6al-4v assn standard single material response Thread Series Designator: Unjf Specification Data: 80205-nas1154 professional/industrial association standard Shelf Life: N/a Unit Of Measure:	0.250 inches
Thready Qty Per Inch (tpi):   28   Min. Tensile Strength (psi):   160000 pounds per square inch   Countersink Angle:   Between 99.0 degrees and 101.0 degrees   Surface Finish:   32.0 microinches threads   Material:   Titanium alloy uns r54520   Material Specification:   Nas 621, 6al-4v assn standard single material response   Thread Series Designator:   Unjf   Specification Data:   80205-nas1154 professional/industrial association standard   Shelf Life:   N/a   Unit Of Measure:	Grip Length:
28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: 132.0 microinches threads 132.0 microinches threads 133.0 microinches threads 134.0 microinches threads 134.0 microinches threads 135.0 microinches t	1.500 inches
Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy uns r54520 Material Specification: Nas 621, 6al-4v assn standard single material response Thread Series Designator: Unjf Specification Data: 80205-nas1154 professional/industrial association standard Shelf Life: N/a Unit Of Measure:	Thready Qty Per Inch (tpi):
160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy uns r54520 Material Specification: Nas 621, 6al-4v assn standard single material response Thread Series Designator: Unjf Specification Data: 80205-nas1154 professional/industrial association standard Shelf Life: N/a Unit Of Measure:	28
Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy uns r54520 Material Specification: Nas 621, 6al-4v assn standard single material response Thread Series Designator: Unjf Specification Data: 80205-nas1154 professional/industrial association standard Shelf Life: N/a Unit Of Measure:	Min. Tensile Strength (psi):
Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy uns r54520 Material Specification: Nas 621, 6al-4v assn standard single material response Thread Series Designator: Unjf Specification Data: 80205-nas1154 professional/industrial association standard Shelf Life: N/a Unit Of Measure:	160000 pounds per square inch
Surface Finish: 32.0 microinches threads Material: Titanium alloy uns r54520 Material Specification: Nas 621, 6al-4v assn standard single material response Thread Series Designator: Unjf Specification Data: 80205-nas1154 professional/industrial association standard Shelf Life: N/a Unit Of Measure:	Countersink Angle:
32.0 microinches threads Material: Titanium alloy uns r54520 Material Specification: Nas 621, 6al-4v assn standard single material response Thread Series Designator: Unjf Specification Data: 80205-nas1154 professional/industrial association standard Shelf Life: N/a Unit Of Measure:	Between 99.0 degrees and 101.0 degrees
Material:Titanium alloy uns r54520Material Specification:Nas 621, 6al-4v assn standard single material responseThread Series Designator:UnjfSpecification Data:80205-nas1154 professional/industrial association standardShelf Life:N/aUnit Of Measure:	Surface Finish:
Titanium alloy uns r54520 Material Specification: Nas 621, 6al-4v assn standard single material response Thread Series Designator: Unjf Specification Data: 80205-nas1154 professional/industrial association standard Shelf Life: N/a Unit Of Measure:	32.0 microinches threads
Material Specification: Nas 621, 6al-4v assn standard single material response Thread Series Designator: Unjf Specification Data: 80205-nas1154 professional/industrial association standard Shelf Life: N/a Unit Of Measure:	Material:
Nas 621, 6al-4v assn standard single material response <b>Thread Series Designator:</b> Unjf <b>Specification Data:</b> 80205-nas1154 professional/industrial association standard <b>Shelf Life:</b> N/a <b>Unit Of Measure:</b>	Titanium alloy uns r54520
Thread Series Designator: Unjf Specification Data: 80205-nas1154 professional/industrial association standard Shelf Life: N/a Unit Of Measure:	Material Specification:
Unjf <b>Specification Data:</b> 80205-nas1154 professional/industrial association standard <b>Shelf Life:</b> N/a <b>Unit Of Measure:</b>	Nas 621, 6al-4v assn standard single material response
Specification Data: 80205-nas1154 professional/industrial association standard Shelf Life: N/a Unit Of Measure:	Thread Series Designator:
80205-nas1154 professional/industrial association standard Shelf Life: N/a Unit Of Measure:	Unjf
Shelf Life: N/a Unit Of Measure:	Specification Data:
N/a Unit Of Measure: 	80205-nas1154 professional/industrial association standard
Unit Of Measure:	Shelf Life:
	N/a
 Demilitarization:	Unit Of Measure:
Demilitarization:	
	Demilitarization:
No	No

## NSN 5305-00-929-4093

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

