

View Online at <https://aerobasegroup.com/nsn/5305-00-929-9212>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.339 inches and 0.386 inches

Fastener Length:

Between 1.921 inches and 1.948 inches

Head Style:

Crowned hexagon

Head Height:

Between 0.194 inches and 0.204 inches

Width Between Flats:

Between 0.554 inches and 0.564 inches

Locking Feature:

Detent ball grip

Grip Diameter:

Between 0.3733 inches and 0.3742 inches

Shank Unthreaded Hole Diameter:

0.106 inches second hole and 0.116 inches second hole

Internal Drive Style:

Slot

Thread Diameter:

0.375 inches

Grip Length:

Between 1.562 inches and 1.582 inches

Thready Qty Per Inch (tpi):

24

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.790 inches second hole and 1.837 inches second hole

Special Features:

Two spring loaded balls in shank as self retaining feature

Material:

Steel

Surface Treatment:

Cadmium

Surface Treatment Specification:

Fs251, fscm 8827 mfr ref single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0