NSN 5305-00-929-9215

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-929-9215

| Thread Class: |
|--|
| За |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.268 inches and 0.315 inches |
| Fastener Length: |
| Between 1.350 inches and 1.377 inches |
| Head Style: |
| Crowned hexagon |
| Head Height: |
| Between 0.131 inches and 0.141 inches |
| Width Between Flats: |
| Between 0.429 inches and 0.439 inches |
| Grip Diameter: |
| Between 0.2483 inches and 0.2492 inches |
| Shank Unthreaded Hole Diameter: |
| 0.076 inches first hole and 0.086 inches first hole |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 1.062 inches and 1.082 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Special Features: |
| Two spring loaded balls in shank as self retaining feature |
| Material: |
| Steel |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Fs251 fscm 88277 mfr ref single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 5305-00-929-9215

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

