NSN 5305-00-930-3470

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-930-3470 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.620 inches **Fastener Length:** 2.250 inches **Head Style:** Knurled no. 2 **Head Diameter:** 0.560 inches **Head Height:** 0.470 inches **Hole Diameter:** 0.062 inches **First Diameter From Head:** 0.250 inches **Second Diameter From Head:** 0.230 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.890 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.940 inches Point Style: Flat **Thread Diameter:** 0.250 inches **Hole Quantity: Hole Type:** Thready Qty Per Inch (tpi): 20 **Hole Configuration Style: Externally Relieved Body Diameter Quantity:** 1 **Product Name:**

Navy special project

Material:

Steel comp 303 or steel comp 303se

NSN 5305-00-930-3470

Thumbscrew - Page 2 of 2

Fiig: A003b0



Material Specification:
Qq-s-764 federal specification all material responses
Surface Treatment:
Passivate
Surface Treatment Specification:
+4ahc1, fscm 02989 mfr ref single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No