3a

32

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-930-5291



## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.465 inches and 0.529 inches Fastener Length: Between 0.609 inches and 0.641 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.311 inches and 0.359 inches Locking Feature: Pellet threads Internal Drive Style: Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: 0.094 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 84.0 degrees Material: Steel **Material Specification:** 66 federal standard single material response Surface Treatment: Zinc **Surface Treatment Specification:** Qq-z-325, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 4 type

## NSN 5305-00-930-5291

Socket Head Cap Screw - Page 2 of 2



## Departure From Cited Designator:

As modified by locking feature

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0