

View Online at <https://aerobasegroup.com/nsn/5305-00-930-5327>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.810 inches and 0.904 inches

Fastener Length:

Between 0.984 inches and 1.016 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.311 inches and 0.359 inches

Locking Feature:

Pellet threads

Internal Drive Style:

Hexagon

Thread Diameter:

0.164 inches

Width Across Flats:

0.094 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

130000 pounds per square inch

Countersink Angle:

Between 80.0 degrees and 84.0 degrees

Material:

Steel

Material Specification:

66 federal standard single material response

Surface Treatment:

Zinc

Surface Treatment Specification:

Qq-z-325, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

4 type

Departure From Cited Designator:

As modified by locking feature

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0