NSN 5305-00-931-4344

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-931-4344 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.200 inches **Fastener Length:** 0.773 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.625 inches **Head Height:** 0.187 inches **First Diameter From Head:** Between 0.220 inches and 0.240 inches **Second Diameter From Head:** Between 0.081 inches and 0.086 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.250 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.573 inches **Point Style:** Flat **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 **Material Specification:** Qq-s-764 cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-931-4344

Thumbscrew - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.