NSN 5305-00-931-5340

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-931-5340 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.221 inches **Fastener Length:** 0.719 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.313 inches **Head Height:** 0.188 inches **First Diameter From Head:** 0.095 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.438 inches **Internal Drive Style:** Slot **End Application:** W/s: aircraft, eagle f-15; submarine acoustic sonar systems; sonar, an/bsy- (v); ship, ohio class ssn (trident); ground mobile force satellite comm term (an/tsc-93a); traffic jam, am/tlq-17a; aircraft, awacs, e-3a; aircraft, hawkeye e-2c; ground mobile force satellite comm term (an/tsc-85a); tacsatcom, an/tsc-85 and an/tsc-93) **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity: Special Features:** Purchase order must specify burr free Material: Steel comp 303 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unc

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-00-931-5340

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0