## NSN 5305-00-931-8613

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-931-8613 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.406 inches **Fastener Length:** 0.906 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.500 inches **Head Height:** 0.205 inches **First Diameter From Head:** 0.150 inches **Second Diameter From Head:** 0.190 inches **Third Diameter From Head:** 0.150 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.250 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.312 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.375 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 3 Material: Steel comp 1211 **Material Specification:** Sae assn standard single material response **Surface Treatment:** Nickel

Thread Series Designator: Unc

## NSN 5305-00-931-8613

Externally Relieved Body Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0