NSN 5305-00-932-0858

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-932-0858 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.859 inches and 1.906 inches **Fastener Length:** Between 1.984 inches and 2.031 inches **Head Style:** Flat chamfer **Head Diameter:** Between 1.107 inches and 1.125 inches **Head Height:** Between 0.740 inches and 0.750 inches **Locking Feature:** Pellet threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.750 inches Width Across Flats: 0.625 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:**

Unf

Specification Or Standard:

6 type

NSN 5305-00-932-0858

Socket Head Cap Screw - Page 2 of 2



Shelf L	ife:
---------	------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-18240 spec.