NSN 5305-00-932-1892

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-932-1892 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.266 inches **Fastener Length:** Between 0.234 inches and 0.266 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.112 inches and 0.118 inches **Head Height:** Between 0.070 inches and 0.073 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.073 inches Width Across Flats: Between 0.062 inches and 0.063 inches Thready Qty Per Inch (tpi): 64 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc **Specification Data:** 80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-00-932-1892

Socket Head Cap Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0