NSN 5305-00-932-2110

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-932-2110 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 0.720 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.085 inches and 0.096 inches **First Diameter From Head:** Between 0.106 inches and 0.110 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.470 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** 30 degrees cone or standard flat point and 63 microinches finish grip Material: Stainless steel **Material Specification:** Qq-s-763 300 series federal specification single material response or comp 16-18 assn standard single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 cl 2 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-932-2110

Externally Relieved Body Screw - Page 2 of 2



_										
וו	0	m	ш	м	•	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.