Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-932-2110

Thread C	lass:
2a	
Thread D	irection:
Right-han	d
Thread L	ength:
0.250 incl	nes
Fastener	Length:
0.720 incl	nes
Head Sty	le:
Pan no. 2	
Head Dia	meter:
Between	0.306 inches and 0.322 inches
Head Hei	ght:
Between	0.085 inches and 0.096 inches
First Diar	neter From Head:
Between	0.106 inches and 0.110 inches
Distance	From Largest Bearing Surface Of Head To End Of First Diameter:
0.470 incl	nes
Internal D	Drive Style:
Slot	
Thread D	iameter:
0.164 incl	nes
Thready	Qty Per Inch (tpi):
32	
Externall	y Relieved Body Diameter Quantity:
1	
Special F	eatures:
30 degree	es cone or standard flat point and 63 microinches finish grip
Material:	
Stainless	steel
Material S	Specification:
Qq-s-763	300 series federal specification single material response or comp 16-18 assn standard single material response
Surface 1	reatment:
Oxide	
Surface 1	reatment Specification:
Mil-c-1392	24 cl 2 military specification single treatment response
Thread S	eries Designator:
Unc	
Shelf Life	
N/a	
Unit Of M	easure:

---

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.