## NSN 5305-00-932-3960

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-932-3960 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.250 inches **Fastener Length:** Between 3.190 inches and 3.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.550 inches and 0.562 inches **Head Height:** Between 0.368 inches and 0.375 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: Between 0.312 inches and 0.316 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp xm-7

**Material Specification:** 

66 federal standard 1st material response or 66 federal standard 2nd material response or 66 federal standard 3rd material response or 66 federal standard 4th material response or astm a493 assn standard 5th material response

**Surface Treatment:** 

**Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

## NSN 5305-00-932-3960

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0