NSN 5305-00-932-5626



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-932-5626 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.630 inches and 0.697 inches **Fastener Length:** Between 1.640 inches and 1.687 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.626 inches and 0.672 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.437 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 215000 pounds per square inch Hardness Rating: Between 45.0 rockwell c and 49.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 431 **Screw Material Specification:** Mil-s-18732 military specification single material response **Screw Surface Treatment:** Chromium **Screw Surface Treatment Specification:** Ams 2401 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a **Unit Of Measure: Demilitarization:** No Fiig: A500d0

NSN 5305-00-932-5626

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-18732 spec.