NSN 5305-00-932-5629

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-932-5629 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.380 inches and 0.447 inches **Fastener Length:** Between 0.577 inches and 0.624 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.280 inches and 0.303 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 215000 pounds per square inch Hardness Rating: Between 45.0 rockwell c and 49.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Navy special project **Screw Material:** Steel comp 431 **Screw Material Specification:** Mil-s-18732 military specification single material response **Screw Surface Treatment:** Chromium **Screw Surface Treatment Specification:** Ams 2401 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-00-932-5629

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-18732 spec.