NSN 5305-00-932-5636



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-932-5636 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.755 inches and 0.812 inches **Fastener Length:** Between 1.890 inches and 1.937 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.711 inches and 0.759 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.5000 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 215000 pounds per square inch Hardness Rating: Between 45.0 rockwell c and 49.0 rockwell c **Countersink Angle:** 100.0 degrees **Screw Material:** Steel comp 431 **Screw Material Specification:** Mil-s-18732 military specification single material response **Screw Surface Treatment:** Chromium **Screw Surface Treatment Specification:** Ams 2401 assn standard single treatment response **Thread Series Designator:** Unjef Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

Fiig:

A500d0

NSN 5305-00-932-5636

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-18732 spec.