

View Online at <https://aerobasegroup.com/nsn/5305-00-933-1359>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.355 inches and 0.395 inches

**Fastener Length:**

Between 0.865 inches and 0.885 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.371 inches and 0.385 inches

**Internal Drive Style:**

Clutch type i

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 99.0 degrees and 100.0 degrees

**Screw Material:**

Steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 431

**Screw Material Specification:**

Mil-s-6050 military specification 1st material response or mil-s-6098 military specification 2nd material response or mil-s-6758 military specification 3rd material response or mil-s-18732 military specification 4th material response

**Screw Surface Treatment:**

Cadmium

**Screw Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-s-6050 spec.