## NSN 5305-00-933-4181

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-933-4181 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.234 inches and 0.266 inches **Fastener Length:** Between 0.898 inches and 0.930 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.340 inches and 0.385 inches First Diameter From Head: Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.648 inches and 0.676 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 81.0 degrees and 83.0 degrees **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Cone point 60 degrees of angle by 0.164 in. Lg Material: Steel comp 303 **Material Specification:** Astm a582 cond a assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-00-933-4181

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0