

View Online at <https://aerobasegroup.com/nsn/5305-00-933-4181>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.234 inches and 0.266 inches

**Fastener Length:**

Between 0.898 inches and 0.930 inches

**Head Style:**

Oval countersunk

**Head Diameter:**

Between 0.340 inches and 0.385 inches

**First Diameter From Head:**

Between 0.125 inches and 0.135 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.648 inches and 0.676 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 81.0 degrees and 83.0 degrees

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Cone point 60 degrees of angle by 0.164 in. Lg

**Material:**

Steel comp 303

**Material Specification:**

Astm a582 cond a assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0