NSN 5305-00-934-0053

Shoulder Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-934-0053



Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.343 inches and 0.363 inches

Fastener Length:

1.928 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.419 inches and 0.437 inches

Head Height:

Between 0.209 inches and 0.219 inches

Shoulder Diameter:

0.3085 inches first shoulder and 0.3105 inches first shoulder

Shoulder Length:

1.495 inches first shoulder and 1.505 inches first shoulder

Internal Drive Style:

Hexagon

Thread Diameter:

0.250 inches

Width Across Flats:

0.156 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

32.0 rockwell c and 43.0 rockwell c

Shoulder Shape:

Round first shoulder

Material:

Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740

Material Specification:

Sae assn standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unc

NSN 5305-00-934-0053

Shoulder Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

