NSN 5305-00-934-0114

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-934-0114



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.408 inches and 0.500 inches Fastener Length: Between 0.470 inches and 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches Hole Diameter: Between 0.033 inches and 0.039 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Hole Quantity: 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 155000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:**

Cadmium and chromate

NSN 5305-00-934-0114

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0