NSN 5305-00-934-0269

Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-934-0269

| Thread Cl | lass: |
|----------------|---|
| 2a | |
| Thread Di | irection: |
| Right-hand | d |
| Thread Le | ength: |
| 0.343 inch | nes |
| Fastener | Length: |
| 0.343 inch | ies |
| Head Styl | le: |
| Flat counter | ersunk undercut |
| Head Diar | meter: |
| Between 0 | 0.340 inches and 0.375 inches |
| Head Heig | ght: |
| 0.050 inch | nes |
| Internal D | Prive Style: |
| Cross rece | ess type 1 |
| Thread Di | iameter: |
| 0.138 inch | ies |
| Thready C | Qty Per Inch (tpi): |
| 32 | |
| Countersi | ink Angle: |
| Between 9 | 99.0 degrees and 101.0 degrees |
| Special F | eatures: |
| Furnished | w/one polytetrafluoroethylene shim and w/one buna-n rubber o ring, underside of head grooved to accommodate furnished items |
| Material: | |
| Steel | |
| Surface T | reatment: |
| Cadmium | and chromate |
| Thread Se | eries Designator: |
| Unc | |
| Shelf Life | |
| N/a | |
| Unit Of M | easure: |
| Demilitari | ization: |
| No | |
| Fiig: | |
| - | |