## NSN 5305-00-934-0288

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-934-0288 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.187 inches **Fastener Length:** 1.562 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.270 inches **Head Height:** Between 0.102 inches and 0.113 inches **First Diameter From Head:** 0.156 inches **Second Diameter From Head:** 0.265 inches **Third Diameter From Head:** 0.088 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.969 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.062 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 1.375 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Qq-s-763 federal specification single material response

**Surface Treatment:** 

**Passivate** 

**Surface Treatment Specification:** 

Mil-f-14072, finish e300 military specification single treatment response

## NSN 5305-00-934-0288

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-f-14072 spec.